

IOIOBox – Enclosure Build Questionnaire

1. Enclosure Size

Bantam

- 28.5”H x 26”W x 21”D
- 6U Standard (22U Maximum)

Original

- 42.3”H x 26.1”W x 25.0”D
- 12U Standard (38U Maximum)

2. Rear Door Option

Airtight - Solid rear door, makes an airtight enclosure.

Vented - Passive dual vents

AC300+Heat Kit - 300W AC Unit (power supply not included)

Barebones

+ Bantam Rear Door

+ Original Rear Door

AC600+Heat Kit - 600W AC Unit – Not compatible with Bantam model (power supply not included)

Barebones

+ Original Rear Door

3. Cable Ingress/Egress Options:

Standard (Aluminum Plate + M12/M20 Cable Glands)



Cable Hood and Rubber Gasket

Roxtec EZEntry 16/16 Kit

Roxtec EZEntry 24/24 Kit

4. Additional Options

PowerVent Kit – only available with vented rear door option (power supply not included)

24V

48V

Quantity (max 2): _____

Each pair of fans is terminated together into a DC female adapter. Also included, is an ethernet adapter for use with a POE injector or switch. Supports 2 per IOIOBox.

Steel Mount Kit - Used for mounting to vertical surfaces like poles, walls, or towers

*** This kit does not include hardware to attach the plates to your structure.***

Din Rail Kit - The perfect size to fit the front door mounting points

Quantity (max 4): _____

DIN Heater (power supply not included)

Illumination Kit - Includes LED bar accessory that mounts to ceiling (power supply not included)

Quantity (max 2): _____

Upper U Rack Expansion Kit

Lower U Rack Expansion Kit

Quantity (max 2): _____

Wood Backer

Please email your completed form to sales@mbsiwav.com or direct to your sales representative to receive pricing.